

Çekomastik 888

Acetoxy Silicone Sealant

Product Description:

Çekomastik 888 Universal Silicone, is a polysiloxane-based, multi-purpose, acetoxy silicone sealant material that is hardened with the air.

Areas of applications:

- Suitable for glazing and sealing
- In window frames and case gaps
- In glass installation details, shop window, etc.
- In the connections of bath tube/wall, kitchen sink/bench, etc.

Features:

- A ready-to-use, one component sealing material
- Slight acetate odour disappears after dried
- Permanently elastic
- Resistant to aging, weather conditions and UV lights
- Resistant to abrasion
- Unaffected by weather conditions approximately one hour after the application (at 20°C)
- The dried surfaces do not adhere to other materials
- Not overpaintable

Technical data:

Colour	Transparent, white, black, grey, brown
Tensile Strength MPa	≥ 1,1
Elongation @ Break (DIN 53504)	≥ %450
Modulus @ Elongation (100%) MPa (DIN 53504)	≥ 0,2
Shore A Hardness	~ 20
Density (gr/cm ³)	~ 0,95 ± 0,05
The expansion ratio of joints (%)	Approx. 15
Skin Formation Time (min)	10 - 15
Curing Speed	Approx. 2
Heat Resistance	Between -40°C and +100°C
Run Temperature	Between +5°C and +40°C

Technical data are approximately provided according to a temperature of + 20°C and a relative humidity of 50%.

Preparation of the substrate :

- The application surfaces should be strong, sound, stable, clean, dry and grease- and dust-free.
- Both sides can be taped in order to obtain a smooth filling.

Warning: Bostik is only responsible for the product quality and cannot be held responsible for its mis-use except for the recommendations regarding where and/or how the product shall be used. It is not possible to give a guarantee for the results of operations for individual cases, due to multiplicity of possible uses and storage and processing conditions of the product, which are not under our control. Where necessary, the user should make their own tests. Due to local regulations, product performance may vary from country to country. This technical bulletin hereby is valid until it is renewed. BOSTIK's right to amend the products in accordance with technical developments is reserved. In cases concerning the safety of the products, the material safety data sheet (MSDS) containing this information should be consulted.



Akçaburgaz Mh. ALKOP Sit. 1575 Sk. C2 Blok No.5-14 Esenyurt 34555 İst.
Tel. (+90 212) 858 01 26 Fax. (+90 212) 858 01 34
info@bostik.com.tr - www.bostik.com.tr

Application:

- Before the application, the tip of the cartridges is cut and a plastic cap is fixed.
- The tip of the cap is cut according to the width of the surface and fixed to the cartridge gun.
- The joints should be filled at one time and without gaps during the application.
- After the joints are filled with silicone, the surface is smoothened with a spatula by pressing immediately.
- The adhesive tape should be removed afterwards.
- The opened packages should be consumed soon.
- Do not apply outdoors in rainy weather.

Cleaning after the application :

- The contaminated areas and used tools should be cleaned with white spirit or alcohol within 10 minutes.
- It is cleaned only mechanically after cured.

Warning:

Since it contains vinegar acid, eyes should be washed with water before it gets hardened.

Consumption:

The amount of use varies according to the joint sizes.

Width of joints (mm)	Depth of joints (mm)	Length of joints (m) 280 ml cartridges
6	6	~9
9	6	~4,5
12	6	~3,5

Packaging:

In 280 ml cartridges / 25 pcs in one box

Storage:

- They should be protected from water, frost and adverse air conditions.
- They should be kept dry and cool on wooden pallets at between +10°C and +25°C in moisture free conditions.
- The opened products should be consumed immediately.
- Maximum 8 boxes are stacked on each other.
- Shelf life is maximum 1,5 year conditional to complying with the abovementioned storage conditions.

Health and Safety Information

For health and safety instruction, first aid measures and spillage and disposal instructions, see separate Safety Data Sheet.

Warning: Bostik is only responsible for the product quality and cannot be held responsible for its mis-use except for the recommendations regarding where and/or how the product shall be used. It is not possible to give a guarantee for the results of operations for individual cases, due to multiplicity of possible uses and storage and processing conditions of the product, which are not under our control. Where necessary, the user should make their own tests. Due to local regulations, product performance may vary from country to country. This technical bulletin hereby is valid until it is renewed. BOSTIK's right to amend the products in accordance with technical developments is reserved. In cases concerning the safety of the products, the material safety data sheet (MSDS) containing this information should be consulted.



Akçaburgaz Mh. ALKOP Sit. 1575 Sk. C2 Blok No.5-14 Esenyurt 34555 İst.
Tel. (+90 212) 858 01 26 Fax. (+90 212) 858 01 34
info@bostik.com.tr - www.bostik.com.tr